



00X4020E060

110 Delta Drive
 Pittsburgh, PA 15238
 NAFTA Sales: (1)800-245-3984
 HK Sales : (852)3102-9337
 magnetics@spang.com
 www.mag-inc.com



XFlux Permeability (μ)	A_L (nH/T ²)	Core Marking	
		Lot Number	Part Number
60	150 \pm 8%	XXXXXX	X4020E060

	Dimensions		Tolerance (\pm)			Packaging
	(mm)	(in)	(mm)	(in)		
A	42.85	1.686	0.64	0.025		Box Qty= 192 Pcs
B	21.08	0.830	0.33	0.013		
C	15.44	0.608	0.25	0.010		
D	14.91	0.587	-	-	Min	Available Hardware
E	30.35	1.194	-	-	Min	PCB4020N1
F	11.89	0.468	0.25	0.010		00B402021
L	5.94	0.234	-	-	Nom	
M	9.27	0.365	-	-	Min	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 50kHz, 100mT max (mW/cm ³)	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area W_a (mm ²)	Cross Section A_e (mm ²)	Path Length L_e (mm)	Volume V_e (mm ³)	Est. Weight (Ea. Piece) (g)
650	80%	50%	20	276	183	98.4	18,000	61
	75	140						

Notes:	Temperature Rating
	Curie Temp: 700 °C

