

攀登更高峰！

Magnetics目前提供可定制高度的标准磁芯。



- 无需堆叠或粘结
- 铁硅铝, 钕坡莫合金和高磁通三种材质均可接受定制 (已列出Kool Mu零件号)
- 提供特殊高度的定制
- 所有标准磁导率皆可接受定制

零件号	标准系列尺寸	磁导率	A _L (nH/T ²)	尺寸 (毫米/mm)				
				外径处理后 外径处理前	内径处理后 内径处理前	高度处理后 高度处理前	A _e (毫米 ² / mm ²)	L _e (毫米 /mm)
77121A7HT14	120	60	70	17.35	9.53	14	38.4	41.2
				16.59	10.16	12.70		
77120A7HT14	120	125	144	17.35	9.53	14	38.4	41.2
				16.59	10.16	12.70		
77121A7HT20	120	60	105	17.35	9.53	20	57.6	41.2
				16.59	10.16	19.05		
77120A7HT20	120	125	216	17.35	9.53	20	57.6	41.2
				16.59	10.16	19.05		
77848A7HT14	206	60	64	21.08	12.07	14	44.2	50.9
				20.32	12.70	12.70		
77206A7HT14	206	125	136	21.08	12.07	14	44.2	50.9
				20.32	12.70	12.70		
77848A7HT20	206	60	96	21.08	12.07	20	66.3	50.9
				20.32	12.70	19.05		
77206A7HT20	206	125	204	21.08	12.07	20	66.3	50.9
				20.32	12.70	19.05		
77894A7HT14	930	60	88	27.69	14.10	14	76.1	63.5
				26.92	14.73	13.00		
77930A7HT14	930	125	183	27.69	14.10	14	82.1	63.5
				26.92	14.73	14.02		
77935A7HT15	930	75	118	27.69	14.10	15	82.1	63.5
				26.92	14.73	14.02		
77930A7HT15	930	125	197	27.69	14.10	15	82.1	63.5
				26.92	14.73	14.02		
77894A7HT15	930	60	94	27.69	14.10	15	82.1	63.5
				26.92	14.73	14.00		
77935A7HT19	930	75	151	27.69	14.10	19	105.0	63.5
				26.92	14.73	17.96		
77930A7HT19	930	125	253	27.69	14.10	19	105.0	63.5
				26.92	14.73	18.01		
77894A7HT19	930	60	120	27.69	14.10	19	105.0	63.5
				26.92	14.73	17.88		
77894A7HT23	930	60	150	27.69	14.10	23	131.0	63.5
				26.92	14.73	22.35		
77930A7HT23	930	125	314	27.69	14.10	23	131.0	63.5
				26.92	14.73	22.35		
77894A7HT34	930	60	225	27.69	14.10	34	196.0	63.5
				26.92	14.73	33.53		
77930A7HT34	930	125	471	27.69	14.10	34	196.0	63.5
				26.92	14.73	33.53		
77553A7HT19	548	75	128	33.55	19.46	19	110.0	81.4
				32.79	20.09	13.89		
77071A7HT15	548	60	80	33.55	19.46	15	86.0	81.4
				32.79	20.09	14.00		
77553A7HT15	548	75	99	33.55	19.46	15	85.5	81.4
				32.79	20.09	13.89		
77548A7HT15	548	125	167	33.55	19.46	15	86.3	81.4
				32.79	20.09	14.02		
77071A7HT19	548	60	102	33.55	19.46	19	110.0	81.4
				32.79	20.09	17.83		
77548A7HT19	548	125	214	33.55	19.46	19	110.5	81.4
				32.79	20.09	17.98		
77071A7HT22	548	60	122	33.55	19.46	22	131.2	81.4
				32.79	20.09	21.34		
77548A7HT22	548	125	254	33.55	19.46	22	131.2	81.4
				32.79	20.09	21.34		
77071A7HT33	548	60	183	33.55	19.46	33	196.8	81.4
				32.79	20.09	32.00		
77548A7HT33	548	125	381	33.55	19.46	33	196.8	81.4
				32.79	20.09	32.00		

请登陆网站拜访
我们！

www.mag-inc.com

全球销售服务中心

+852 3102 9337

asiasales@spang.com

美国总公司

+1 412 696 1333

magnetics@spang.com